


'S' Type Load Cell




SPECIAL FEATURES

- Good Linearity
- Good Repeatability
- Easy to Install
- Mechanical Overload Protection
- Temp Compensated
- Wide Range
- Good Reliability

SPECIFICATION

Model	LZYA
Rated Load Capacity	1, 5, 10, 50, 30 kgs
Rated Output Sensitivity	2mV/V $\pm$ 0.25%
Input Resistance	400 $\pm$ 25 Ohms
Output resistance	350 $\pm$ 3 Ohms
Excitation Voltage	10 to 15 Volts DC/AC (RMS)
Non Linearity	$\pm$ 0.025% of Rated Output
Hysteresis	$\pm$ 0.025% of Rated Output
Creep	0.025% of Rated Output
Non Repeatability	$\pm$ 0.05% of Rated Output
Zero Balance	2% of Rated Output
Operatable Temperature Range	-20°C to 65°C
Storage temperature Range	-50°C to 85°C
Temperature Effect on Zero	0.005% of Rated Output/°C
Temperature Effect on Output	0.005% of rated Output /°C
Over load rating, Safe	150% of Rated Capacity
Power load rating (Ultimate)	200% of Rated Capacity
Protection Class	IP65






Connection Details

Input	Output
RED (+ve)	GREEN (+ve)
BLACK (-ve)	WHITE (-ve)

Electrical Information



*Specification subject to change without notice



Synopsis Techno Instruments

409/B-Wing, Kemp's Plaza, Chincholi Bunder, Malad (W), Mumbai, India, Pin - 400 064

Contact : +91 22 400 30 704 /06 Email : admin@synapsistechno.in,

www.synapsistechno.in